

**VINTAGE**

1	DESCRIPTION
	Enamel glass mosaic, consisting of 25x25 mm tesserae, 4 mm thick, that are intentionally uneven, with non-linear edges, subtly nuanced colours and surface imperfections.

2	APPLICATIONS	
A	INTERIOR WALLS	Walls and ceilings in general, for residential and public buildings
B	INTERIOR FLOORING	Light traffic (private residential rooms)
C	- EXTERIOR WALLS - SWIMMING POOLS - HIGH-HUMIDITY AREAS (shower, Turkish bath, bio sauna, etc.)	Suitable for all these environments

3	WEIGHTS AND MEASUREMENTS	
	Size	25x25 mm
	Mounting	paper
	Sheet dimensions	313.2x313.2 mm
	Number of tiles/sheet	144
	Thickness	4 mm
	Joint	0÷1.2 mm
	Weight	7.8 kg/sqm
	Quantity/carton	0.98 sqm
	Sheets/carton	10

4	TECHNICAL CHARACTERISTICS			
	Description	Test	Established limits	Result
	Resistance to chemical attack	ISO 10545 - 13		Resistant
	Resistance to thermal shock	ANSI A 137.2-2012	+15/+71°C	Resistant
	Wear resistance (PEI)	ISO 10545 - 7	Class 0 - 5	Class 2
	Colour resistance to fading	DIN 51094		Resistant
	Water absorption	ISO 10545 - 3	E ≤ 0.5%	< 0.5
	Frost resistance	ISO 10545 - 12		Resistant
	Stain resistance	ISO 10545 - 14		Resistant
	Slip resistance	DIN 51097	A(12°-18°) B(18°-24°) C(+24°)	A
	Slip resistance	DIN 51130	R9 - R13	R9

5	STRENGTHS
	<ul style="list-style-type: none"> <li>- easy to clean surface</li> <li>- lightweight and thin, ideal for renovation projects</li> <li>- tiling of curved surfaces: convex surfaces, 30 mm radius - concave surfaces, 50 mm radius</li> </ul>

<b>6</b>	<b>INSTALLATION</b>
<b>A</b>	<p>For proper installation, the substrate must be a perfectly smooth even, white surface, and must be cured, dry, sound and stable.</p> <ul style="list-style-type: none"> <li>- Interior screed or plaster: we recommend Bisazza Ad Hoc+Ultra* adhesive</li> <li>- Other types of substrates: we recommend Bisazza eGlue adhesive</li> <li>- For swimming pool installation, we recommend using the Bisazza Pool Installation System (Ad Hoc+Ultra adhesive and Pool eGrout epoxy grout)</li> <li>- For installation on swimming pools with salt water or thermal spring water, use epoxy products only: we recommend the Bisazza Epoxy Pool Installation System (epoxy eGlue adhesive + Pool eGrout epoxy grout) and waterproofing with epoxy membrane</li> <li>- When laying, use a 3.5 mm toothed trowel. N.B. Attrition tends to wear out the trowel; it is crucial to maintain the proper thickness of the teeth for the entire installation period, restoring it with the flex tool, if necessary.</li> <li>- Thoroughly remove any traces of adhesive before grouting</li> </ul> <p>Average consumption Bisazza Ad Hoc: 1.2 kg/sqm (two coats of skimming included)                  Average consumption Bisazza Ultra: 0.8 kg/sqm                  Average consumption Bisazza eGlue: 1.6 kg/sqm (please add 0.9 Kg/sqm for the skimming)</p> <p>* Except for any specific standards or codes enforced by an individual country.</p>
<b>B</b>	<p><b>Grouting</b>                  For the best results and performance, use Bisazza Fillgel Plus.                  The grout colour will affect the final aesthetic appearance of the installed tile.</p> <p><b>Fillgel 1104 neutro base</b> is a colourless and semi-transparent grout and must be applied with special care. Due to its colourless nature, some yellowing occurs when exposed to sunlight (UV radiation), which becomes more noticeable with time. This is why Fillgel 1104 neutro base <u>cannot be used</u> for exterior applications or in outdoor pools.                  For pools and outdoor use, Bisazza recommends Pool eGrout epoxy grout.</p> <p>Average consumption Bisazza Fillgel Plus: 1 kg/sqm                  Average consumption Bisazza Pool eGrout: 0.9 kg/sqm</p> <p><b>For further information on installation procedures, consult the installation manual and product technical data sheets.</b></p>
<b>7</b>	<b>MAINTENANCE</b>
	<p>Use ordinary cleaning products (except those containing hydrofluoric acid or phosphoric acid), for maintenance and cleaning of glass mosaic surfaces, taking care to rinse thoroughly with water. Alkaline detergents should be used cautiously and quickly rinsed off with water. Cleaning products should never be used on hot surfaces or those directly exposed to sunlight. Avoid using abrasive tools and high-pressure water jets (pressure washing).</p>
<b>8</b>	<b>WARNINGS</b>
	<p>The colour of the mosaic tiles is never perfectly uniform or even. Slight chipping in some tiles is a characteristic feature of the product. Also, please note: it is impossible to guarantee that tile colours in subsequent orders will be identical.</p> <p><b>IMPORTANT:</b> Vintage series tiles are not compatible with those in the other Bisazza mosaic collections. Thus, they cannot be used with blends or decorations.</p> <p>Prior to installation, all materials should be stored in a dry place sheltered from rain and humidity.</p>