

**eRemover PLUS****F9020003**

## Professional product for the removal of hardened Fillgel

13/02/2018

### Product Description

eRemover Plus is a thixotropic paste for the removal of hardened epoxy grout on vertical and horizontal surfaces.

### Specifications

Appearance	: creamy
Colour	: beige
Odour	: characteristic, pungent
Density, UNI 8310	: $0.95 \pm 0.02 \text{ g/cm}^3$
Solubility in water	: completely soluble
Action	: from 6 to 24 hours
Viscosity ISO 3219	: $200 \pm 15 \text{ mPa}\cdot\text{s}$
Solid content	: 10-14%
pH	: 1-2

**Note:** data measured at a temperature of 22° C, 50% RH.

### Instructions for use

#### *Substrate preparation.*

The surface must be clean and dry. Cover any parts that should not come into contact with the product.

#### *Product preparation.*

Mix well to blend the product before use. eRemover Plus is used as supplied.

#### *Application.*

Spread eRemover Plus using a stiff plastic spatula or a brush to an even thickness of approx. 1mm. Cover the surface gradually using a HDPE sheet with a minimum thickness of 10 microns. Leave on for a sufficiently long time (generally between 6 and 24h) based on the temperature and the thickness of the grout to be removed.

#### *Residue removal.*

Lift the cover sheet gradually and remove any surplus eRemover Plus using a rubber spatula, digging deep into the joints with a stiff bristle brush. Wash with warm water and brush all residue away from the joints, which will now be grooved. Continue until the entire area is cleaned of all residue, checking that all marks have been removed. Let the surfaces and joints dry for at least 24h (48h at low temperatures).

#### *Surface finish.*

RegROUT with Fillgel Plus.

## **Indicative yield**

1 m<sup>2</sup>/kg

## **Storage**

The product retains its characteristics for 24 months when stored in a cool, dry place.  
Protect from frost.

## **Warnings**

- Do not use in the presence of polyurethane and epoxy glues (as eGlue).
- Perform preliminary tests of compatibility with the material to be cleaned.
- Do not let eRemover Plus dry on the substrate.
- We recommend spreading eRemover Plus during the cooler hours of the day.
- Do not use on acid-sensitive materials (carbon steel, polished marble and limestone, bronze, etc.).
- Ventilate the room during use.
- Avoid contact with skin.
- Use gloves (EN 374), glasses with side shields (EN 166) and masks with charcoal filters (EN 14387 type A = brown).

*The information provided in this data sheet, given to the best of our knowledge and experience, does not absolve the users from carrying out preliminary tests and trials to check that the product is suitable for the intended use. For further technical information or specific systems and/or applications, contact our TECHNICAL SUPPORT DESK.*

**FOR PROFESSIONAL USE ONLY.**