

THE CRYSTAL COLLECTION

1	DESCRIPTION
	<p><i>The Crystal Collection</i> is the Bisazza collection of 10x10 mm (3/4"x3/4") glass mosaic and gold mosaic decors and blends embellished with Swarovski crystals in the same size.</p> <p>The crystals are produced with a special cut exclusively for Bisazza.</p>

2	APPLICATIONS	
A	INTERIOR WALLS	walls and ceilings in general, of any shape and size, for residential and public buildings
B	FLOORS	<u>not suitable</u>
C	<ul style="list-style-type: none"> - EXTERNAL WALLS - SWIMMING POOLS - HUMID AREAS (shower, bio sauna, spa, etc.) 	<u>not suitable</u>

3	WEIGHTS AND MEASUREMENTS	
	Size	10x10 mm
	Mounting	paper
	Sheet dimensions	322x322 mm
	Number of tiles/sheet	900
	Thickness	4 mm
	Joint	0.76 mm
	Weight	7 kg/m ²
	Quantity/carton	1.03 sqm*
	Sheets/carton	10*

*these quantities refer to blends. For decorations, please check on catalogue.

4	TECHNICAL CHARACTERISTICS
	Not available

5	STRENGTHS
	<ul style="list-style-type: none"> - possibility of customisation since the crystals are compatible with all 10x10 mm Bisazza Collections - ease of surface cleaning - light weight and thinness allows for easy renovations - colour brightness due to high refractive index - tiling of curved surfaces: convex, 20 mm radius - concave, 20 mm radius

6	INSTALLATION
A	<p>For best results, the foundation must have a perfectly smooth, even surface, and must be dry, sound and stable. Never use cement based products for installation and grouting.</p> <p>The Crystal Collection mosaic is always supplied with the Bisazza e-Glue adhesive and Fillgel Plus UVR grout. The company recommends that you always use these products.</p> <p>When laying, use a spatula with 3,5 mm teeth Thoroughly wash the traces of paper glue before grouting. Average consumption Bisazza eGlue: 1.6 kg/sqm (please add 0.9 Kg/sqm for the skimming)</p>
B	<p>Grouting: For the best results and performance, use Bisazza Fillgel Plus UVR. The grout colour will affect the final aesthetic appearance of the product installed. Being a colourless and semi-transparent grout, Fillgel 1104 neutro base needs to be used with special care. Because of its colourless feature, the yellowing due to UV rays exposure becomes more visible with time. For this reason, Fillgel 1104 neutro base cannot be used outdoors and in outdoor swimming-pools. Average consumption Bisazza FILLGEL PLUS UVR: 1.45 kg/sqm</p> <p>For any information on the installation procedure, consult the installation book and the products technical data sheets.</p>

7	MAINTENANCE
	<p>Use ordinary cleaning products for maintenance and cleaning of glass mosaic surfaces (except those containing hydrofluoric acid or phosphoric acid), being careful to rinse thoroughly with water. Alkaline detergents should be used carefully and rapidly rinsed out with water. Any cleaning product should not be used on heated or directly exposed to sunrays surfaces. Avoid using abrasive tools and high pressure jets of water.</p>

8	WARNINGS
	<p>Before the application, all the materials should be stored in a dry place sheltered from rain and humidity. Not suitable for flooring, outdoor use, swimming pools and humid areas.</p>