

# BISAZZA

## **Declaration of performance**

According to Annex III of the Regulation (EU) No. 305/2011

DOP B 16/001 EN

1. Unique identification code of the product-type:

**eGlue**

2. Type, batch or serial number or any other element allowing identification of the construction product as required pursuant to Article 11(4):

**Batch No.: see packaging of the product**

3. Intended use or uses of the construction product, in accordance with the applicable harmonized technical specification, as foreseen by the manufacturer:

**REACTION RESIN ADHESIVE WITH IMPROVED CHARACTERISTICS AND REDUCED SLIP (R2T)  
FOR INDOOR AND OUTDOOR TILING ON FLOORING AND WALLS**

4. Name, registered trade name or registered trade mark and contact address of the manufacturer as required pursuant to Article 11(5):

**BISAZZA S.p.A.  
Viale Milano, 56 – 36075 Alte di Montecchio Maggiore (VI) – ITALY  
www.bisazza.com**

5. Where applicable, name and contact address of the authorized representative whose mandate covers the tasks specified in Article 12(2):

**Not applicable**

6. System or systems of assessment and verification of constancy of performance of the construction product as set out in Annex V:

**System 3**

7. In case of the declaration of performance concerning a construction product covered by a harmonized standard:

**The notified body ELLETIPI S.R.L., ID No. 1308 performed the determination of the product type on the basis of type testing under system 3 and issued the testing reports No. 32604/16, 32605/16, 32606/16, 32607/16 and 32608/16.**

**The notified body LAPI S.p.A., ID No. 0987 performed the determination of Reaction to Fire on the basis of type testing under system 3 and issued the testing report No. 2086.0DC0050/15.**

# BISAZZA

8. In case of the declaration of performance concerning a construction product for which a European Technical Assessment has been issued:

**Not applicable**

9. Declared performance

Essential characteristics	Performance	Harmonized technical specification
Reaction to fire	Class E, Efl	EN 12004:2007+A1:2012
Initial shear adhesion strength	$\geq 2,0 \text{ N/mm}^2$	
Shear adhesion strength after water immersion	$\geq 2,0 \text{ N/mm}^2$	
Open time: tensile adhesion strength (after 30 minutes)	$\geq 0,5 \text{ N/mm}^2$	
Reduced slip	$\leq 0,5 \text{ mm}$	
Shear adhesion strength after thermal shock	$\geq 2,0 \text{ N/mm}^2$	
Dangerous substances	Refer to SDS	


10. The performance of the product identified in points 1 and 2 is in conformity with the declared performance in point 9.

**This declaration of performance is issued under the sole responsibility of the manufacturer identified in point 4.**

Signed for and on behalf of the manufacturer by:

PERISSINOTTO SERGIO - OPERATIONS DIRECTOR  
(name and position)

Vicenza 01/08/2016  
(place and date of issue)

  
(signature)